

# TEXSTYLE

NORDIC TEXTURES

## KAYTO RECYCLED



50% Recycled polyester  
50% Polyester  
430 kg of plastic per 1000 m  
520 g/m<sup>2</sup>  
142 cm



### SPECIFICATIONS

#### Abrasion resistance

ISO 12947-2:2016 > 80.000 rubs.

#### Pilling

EN ISO 12945-2:2000 Rate 4.

#### Colour fastness to light

ISO 105-B02:2014 Rate 5.

#### Colour fastness to rubbing

DIN EN ISO 105-X12:2016-11:  
Wet 5, Dry 5.

#### Resistance to seam slippage

Warp (mm) 3.9, Weft (mm) 4.1.

#### Flame retardant

Ca Tb 117-2013 (USA).

& upon requirement can pass:  
BS 5852 (UK).

#### Performance

Custom requirements will be followed.

#### Environment

REACH.

OEKO-TEX Standard 100.

Formaldehyde Free. EN ISO 14184-1:2011

#### Washability

Easy to clean by hand.

Vacuum clean frequently using a furniture nozzle. Remove stains as soon as they occur using a casual kitchen cloth, soap and mild water. Do not use strong cleaning or bleaching agents. Machine washable at 30 °.



[textstyle.dk](http://textstyle.dk)