

# TEXSTYLE

NORDIC TEXTURES

## ABOUT RECYCLED OUTDOOR



100% Solution dyed  
GRS Recycled polyester  
260 kg of plastic per 1000 m  
260 g/m<sup>2</sup>  
150 cm



## SPECIFICATIONS

### Abrasion resistance

ASTM D4157 in RUBS: >16.000 rubs.

### Pilling

EN ISO 12945-2:2000 Rate 4.

### Colour fastness to light

ISO 105-B02:2014 Rate 7-8.

AATCC16-1998:

Class 4 @1200hrs.

### Colour fastness to rubbing

DIN EN ISO 105-X12:2016-11:

Wet 4-5 Dry 4-5.

### Resistance to seam slippage

Warp (mm) 2.1, Weft (mm) 1.9

### Flame retardant

Ca Tb 117-2013 (USA).

& upon requirement can pass:

BS 5852 (UK).

### Performance

Custom requirements will be followed.

### Environment

REACH Compliance

OEKO-Tex Standard 100

Formaldehyde Free. EN ISO 14184-1:2011

### Washability

Easy to clean by hand.

Vacuum clean frequently using a furniture nozzle. Remove stains as soon as they occur using a casual kitchen cloth, soap and mild water. Do not use strong cleaning or bleaching agents. Machine washable at 30 °.



OEKO-TEX®  
CONFIDENCE IN TEXTILES



texstyle.dk