

# TEXSTYLE

NORDIC TEXTURES

## IBIZA OUTDOOR



100% Solution dyed Acrylic  
340 g/m<sup>2</sup>  
150 cm



### SPECIFICATIONS

#### Abrasion resistance

ASTM D4157 in RUBS: >16.000 rubs.

#### Pilling

EN ISO 12945-2:2000 Rate 4.

#### Colour fastness to light

ISO 105-B02:2014 Rate 8.

AATCC16-1998:

Class 4 @1200hrs.

#### Colour fastness to rubbing

DIN EN ISO 105-X12:2016-11:

Wet 4-5 Dry 4-5.

#### Resistance to seam slippage

Warp (mm) 2.1, Weft (mm) 1.9

#### Flame retardant

Ca Tb 117-2013 (USA).

& upon requirement can pass:

BS 5852 (UK).

#### Performance

Custom requirements will be followed.

#### Environment

REACH Compliance

OEKO-Tex Standard 100

Formaldehyde Free. EN ISO 14184-1:2011

#### Washability

Easy to clean by hand.

Vacuum clean frequently using a furniture nozzle. Remove stains as soon as they occur using a casual kitchen cloth, soap and mild water. Do not use strong cleaning or bleaching agents. Machine washable at 30 °.

texstyle.dk

OEKO-TEX®  
CONFIDENCE IN TEXTILES

