

TEXSTYLE

NORDIC TEXTURES

PALMA OUTDOOR



100% Solution dyed polypropylene
410 g/m²
140 cm



SPECIFICATIONS

Abrasion resistance

ASTM D4157 in RUBS: 45.000 rubs.

Pilling

EN ISO 12945-2:2000 Rate 4.

Colour fastness to light

ISO 105-B02:2014 Rate 8.

AATCC16-1998:

Class 4 @1200hrs.

Colour fastness to rubbing

DIN EN ISO 105-X12:2016-11:

Wet 3 Dry 3-4.

Resistance to seam slippage

Warp (mm) 1, Weft (mm) 4.5

Flame retardant

Ca Tb 117-2013 (USA).

& upon requirement can pass:

BS 5852 (UK).

Performance

Custom requirements will be followed.

Environment

REACH Compliance

OEKO-Tex Standard 100

Formaldehyde Free. EN ISO 14184-1:2011

Washability

Easy to clean by hand.

Vacuum clean frequently using a furniture nozzle. Remove stains as soon as they occur using a casual kitchen cloth, soap and mild water. Do not use strong cleaning or bleaching agents. Machine washable at 30 °.

textstyle.dk

OEKO-TEX®
CONFIDENCE IN TEXTILES

