## TEXSTYLE

NORDIC TEXTURES

## **MOVIE RECYCLED**

100% Recycled polyester 400 kg of plastic per 1000 m 360 g/m<sup>2</sup> 142 cm



## SPECIFICATIONS

Abrasion resistance ISO 12947-2:2016: >100.000 rubs.

Pilling EN ISO 12945-2:2000: Rate 4-5.

<u>Colour fastness to light</u> ISO 105-B02:2014: Rate 5.

<u>Colour fastness to rubbing</u> DIN EN ISO 105-X12:2016-11: Dry 5, Wet 5.

<u>Resistance to seam slippage</u> Warp (mm) 1,7, Weft (mm) 2,5.

<u>Flame retardant</u> Ca Tb 117-2013 (USA): Pass. BS 5852 (UK): Pass upon requirement.

<u>Performance</u> Customer requirements will be followed.

<u>Environment</u> REACH Compliance. OEKO-TEX Standard 100. Formaldehyde Free. EN ISO 14184-1:2011

## <u>Washability</u>

Easy to clean by hand. Vacuum clean frequently using a furniture nozzle. Remove stains as soon as they occur using a casual kitchen cloth, soap and mild water. Do not use strong cleaning or bleaching agents. Machine washable at 30 °.







texstyle.dk